

PG750系列全自动高速双压旋转式压片机

PG750 Series Fully Automatic High Speed Double Press Rotary Tablet Press Machine

► 用途 (Application)

本系列为双边出片、大压力高速压片机，采用先进的无手轮伺服控制模式，简单快捷精度高。
本系列产品具有高精度、高速度、高自动化程序等优点，能压制双层色片、环形片、圆形片、刻字片和异形片，适合于制药、食品、化工等行业的高效、精密压片。

This series is a double-sided tablet press with high pressure and high speed. It adopts advanced handwheel-free servo control mode, which is simple, fast and high-precision.
This series of products has the advantages of high precision, high speed and high automation program. It can press double-layer color tablets, ring tablets, round tablets, engraved tablets and special-shaped tablets. It is suitable for efficient and precise tablet pressing in the pharmaceutical, food, chemical and other industries.



► 特点 (Features)

1. 专用的防渗油、防尘装置。

2. 便于拆卸的结构，确保设备可维护性。

3. 自动润滑系统，使各部位润滑更精准。

4. 采用压臂式加压方式，加压快捷力矩大。

5. 定量导轨加长，可控制冲头支数增加，片重更精准。

6. 多层三浆强迫加料装置，使物料充填更均匀。

7. 剔废系统：系统可以进行单片自动剔废和批量自动剔废。
1. Special anti-oil and dust-proof device.

2. Easy-to-disassemble structure to ensure the maintainability of the equipment.

3. Automatic lubrication system to make lubrication of each part more accurate.

4. Adopting the pressure arm type pressurization method, the pressurization is fast and the torque is large.

5. The quantitative guide rail is lengthened to control the increase in the number of punches and the tablet weight is more accurate.

6. Multi-layer three-slurry forced feeding device to make the material filling more uniform.

7. Waste rejection system: The system can automatically reject single pieces and batches of waste.



► 技术参数 (Technical Parameters)

参数ITEM	型号TYPE	PG-45	PG-55	PG-69	PG-75
冲模类型 Tooling Type	-	D	B	BB	BB
冲模数 Dies	sets	45	55	69	75
最大压片直径 Max.Dia of Tablet	mm	25	16	13	13
最大异形长轴尺寸Max abnormal prolate axis size	mm	25	18	16	16
最大产量 Max. Output	Tablet/h	390000	470000	580000	630000
最大充填深度 Max.Depth of Fill	mm	20	18	18	18
最大主压力 Max Main Pressure	kn	100			
最大预压力 Max Pre-pressure	kn	20			
电源 Power	-	380y,50hz 10.5-13kw			
外形尺寸 Overall Size (L*W*H)	mm	1260*1260*1950			
主机重量 Net Weight	kg	3750			
可选购压制双压片或环形片功能(根据客户需求) Double-layer tablet or ring tablet function(for your choice)					