

DPB-260/320平板式铝塑泡罩包装机

DPB-260/320 Flat-plate Blister Packing Machine

► 用途 (Application)

本产品是目前新一代改进型泡罩包装设备，适应性强广泛用于制药，食品，医疗器械，电子等企业的胶囊，片剂，大密丸，奶片，糖果以及电子元件等铝铝，铝塑，纸塑复合密封包装。结构独特、简洁耐用，换模具方便，适应各种形状大小版块。

This product is a new generation of improved blister packaging equipment, with strong adaptability and is widely used in aluminum-aluminum, aluminum-plastic, paper-plastic composite sealed packaging of capsules, tablets, large-density pills, milk tablets, candies and electronic components in pharmaceutical, food, medical equipment, electronics and other enterprises. It has a unique structure, is simple and durable, and is easy to change molds, and is suitable for various shapes and sizes.



► 特点 (Features)

1. 平板成型适合各种异型泡型，泡罩挺括，平板热封网纹均匀。

2. 核心电器采用PLC控制，温度模块，人机界面控制，产品档次高，扩展空间大，配备光标对位装置。

3. 各模块箱体均采用专用设备加工，保证精度，互换性强。
1. Flat plate forming is suitable for various special-shaped bubbles, the blister is crisp, and the flat plate heat-sealed mesh is uniform.

2. The core electrical appliances are controlled by PLC, temperature module, and human-machine interface. The product is of high grade and has large expansion space. It is equipped with a cursor registration device.

3. Each module box is processed by special equipment to ensure accuracy and strong interchangeability.



► 技术参数 (Technical Parameters)

参数ITEM	型号TYPE	DPB-260	DPB-320
冲裁次数 Cutting Frequency	times/min	6-35 (I) 20-60(II)	20-50
生产能力 Production Capacity	strip/h	8400 (I) 12000(II)	15000(standard blister sheet 80*57)
最大成型面积及深度 Max Shaping Areas and Depth	mm	240*160*26	320*160*26
行程范围 Stroke	mm	20-120 (可按用户要求设计can be manufactured as user's requirements)	
标准版块 Standard Sheet	mm	87*57 (可按用户要求设计can be manufactured as user's requirements)	80*57 80*35 95*65 105*42 105*55
空气压力 Air Pressure	-	0.4-0.6mpa	0.5-0.7mpa 0.2m3/min
总电源 Total Power	-	380V/220V 50HZ 6KW	380V/220V 50Hz 8kw
主电机功率 Main Motor Power	kw	1.5	1.5
PVC硬片 PVC Hard Pieces	mm	0.15 - 0.5*250	0.15 - 0.5*320
PTP铝箔 PTP Aluminum Foil	mm	0.02 - 0.035*250	0.02 - 0.035*320
透析纸 Dialysis Paper	mm	50 - 100g*250mm	50 - 100g*320
模具冷却 Mould Cooling	mm	自来水或循环水tap water or recycled water	自来水或循环水tap water or recycled water
外形尺寸 Overall Size	mm	2710*720*1600	2910*820*1600
机器净重 Net Weight	kg	1700	2200